



XEWR8.E204632

Thermal-device-protected Motors Certified for Canada - Component

Page Bottom

Thermal-device-protected Motors Certified for Canada - Component

See General Information for Thermal-device-protected Motors Certified for Canada - Component

GGM CO LTD

E204632

327-3 SONGNAE-DONG

SOSA-KU

BUCHUN-SI, KYONGGI-DO 422-400 REPUBLIC OF KOREA

Thermally protected motors, Model(s) 6115A1, 6115A2, 6115AD, 6120A1, 6120A2, 6120AD, 6120B1-H, 6120B1-T, 6120B2-H, 6120B2-T, 6125A1, 6125A2, 6125AD, 6125P1, 6125P2, 6130A1, 6130A2, 6130AD, 6140A1, 6140A2, 6140AD, K7IG15NU, K7IP15NU, K7IS15NU, K7RG15NU, K7RP15NU, K7RS15NU, K8I(+)25NH, K8I(+)25NH-B, K8I(+)25NH-T, K8I(+)25NH-T5, K8I(+)25NH.1, K8IG25NU, K8IP25NU, K8IS25NU, K8RG25NU, K8RG25NU-B, K8RP25NU, K8RP25NU-B, K8RS25NU, K8RS25NU-B, K9I(+)200FH, K9I(+)200FH-B, K9I(+)200FH-T, K9I(+)200FH-T5, K9I(+)200FH.1, K9I(+)40NH, K9I(+)40NH-B, K9I(+)40NH-T, K9I(+)40NH-T5, K9I(+)40NH.1, K9I(+)60FC-SP,SU, K9I(+)60FH, K9I(+)60FH-B, K9I(+)60FH-T, K9I(+)60FH-T5, K9I(+)60FH.1, K9I(+)90FH, K9I(+)90FH-B, K9I(+)90FH-T, K9I(+)90FH-T5, K9I(+)90FH.1, K9IG120FC-2P, K9IG120FU, K9IG120FU-2P, K9IG180FU, K9IG40NU, K9IG60FC, K9IG60FU, K9IG90FC, K9IG90FU, K9IP120FC-2P, K9IP120FU, K9IP120FU-2P, K9IP180FU, K9IP40NU, K9IP60FC, K9IP60FU, K9IP90FC, K9IP90FU, K9IS120FC-2P, K9IS120FU, K9IS120FU-2P, K9IS180FU, K9IS40NU, K9IS60FC, K9IS60FU, K9IS90FC, K9IS90FU, K9RG120FU, K9RG180FU, K9RG40NU, K9RG60FC, K9RG60FU, K9RG90FC, K9RG90FU, K9RP120FU, K9RP180FU, K9RP40NU, K9RP60FC, K9RP60FU, K9RP90FC, K9RP90FU, K9RS120FU, K9RS180FU, K9RS40NU, K9RS60FC, K9RS60FU, K9RS90FC, K9RS90FU

Model No.	Output	Hz/DC	Volts	FL Amps	Service Factor	SF Amps	Poles	Number of Speeds	RPM	Capacitor Rating	Phases	Ins Class	Duty	Prot. Type	Rated Ambient (°C)
(click on a model number to see complete product details)															
K8I (+) 25NH or B or T or T5	25W	50	220-240	0.28-0.33	-	-	4	1	1350	-	3	B	Cont	TP	40
	25W	60	220-240	0.24-0.27	-	-	4	1	1600	-	3	B	Cont	TP	40
K9I (+) 200FH or B or T or T5	200W	50	220-230	1.36-1.51	-	-	4	1	1350	-	3	B	Cont	TP	40
	200W	60	220-230	1.06-1.15	-	-	4	1	1600	-	3	B	Cont	TP	40
K9I (+) 40NH or B or T or T5	40W	50	220-240	0.33-0.42	-	-	4	1	1350	-	3	B	Cont	TP	40
	40W	60	220-240	0.31-0.35	-	-	4	1	1600	-	3	B	Cont	TP	40
K9I (+) 60FH or B or T or T5	60W	50	220-240	0.55-0.66	-	-	4	1	1350	-	3	B	Cont	TP	40
	60W	60	220-240	0.47-0.53	-	-	4	1	1600	-	3	B	Cont	TP	40
K9I (+) 90FH or B or T or T5	90W	50	220-240	0.72-0.93	-	-	4	1	1350	-	3	B	Cont	TP	40
	90W	60	220-240	0.63-0.76	-	-	4	1	1600	-	3	B	Cont	TP	40

Marking: Company name or tradename "E204632" , motor type and model (or model designation) and the Recognized Component Mark for Canada,



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".